





G-Series 501 G/701 G





MH 520 501 G



MH 520 701 G/MH 520 701 G NPT

5/2-way double solenoid valve actuated by impulse. Position is kept until an electrical signal is applied to the opposite side even when not attached to electrical source.

The G-Series valves offer the flexibility of in-line fitment as well as the option of being assembled on to a manifold as shown. Manifolds for valves type 501 G are displayed on page 2.7.2.2, manifolds for valves type 701 G are displayed on page 2.7.2.3.

Available with solenoid operators: 230V/50Hz, 110V/50Hz, 24V/50Hz, 48V=, 24V=, 12V=.

Valves are generally equipped with manual override. If requested without manual override please order M 520 _ _ _ .

Valves are also available with external pilot feed.

Type: MEH 520 _ _ _ G. Ports 12 and 14: M5.

Minimum actuation pressure: 2,5 bar. Operating pressure: 0 - 10 bar.

Version for vacuum on request.

Туре	Port size	Air flow	Operating press.	Power consumption	Weight	
MH 520 501 G	G 1/8"	650 I/min	2 - 10 bar	$3 W = / 5 VA \sim$	0,33 kg	€x*
MH 520 701 G	G 1/4"	1250 I/min	2 - 10 bar	$3 W = / 5 VA \sim$	0,35 kg	€X¥MK
MH 520 701 G NPT	1/4" NPT	1250 I/min	2 - 10 bar	$3 W = / 5 VA \sim$	0,35 kg	⟨£x⟩

